


## Features

- 30mm Barrel Style Housing
- M12 Quick Disconnect from driver to remote head
- 31mm length remote head
- Driver built in – No External wiring to a driver
- PNP and NPN Strobe input
- Continuous operation or Strobe mode
- Dimmable via built in potentiometer



Electrical Input	Voltage - 24 VDC +/- 10%    Maximum 6 Watts
Analog Intensity	The output is adjustable from 0-100% of brightness by a 0 -10 VDC signal
Dimmable	The output is manually adjustable from 0-100% of brightness by potentiometer
Continuous Mode	Light will be in continuous mode by leaving signal on strobe input
Strobe	PNP ▶ +5VDC or greater to activate.    NPN ▶ GND (<1VDC) to activate
Strobe Mode	The Light will operate in either continuous or strobe mode. In strobe mode, the output pulse width will track the pulse width of the strobe pulse.

 <p>1 = 24VDC 2 = NPN STROBE 3 = GND 4 = PNP STROBE 5 = 0-10VDC Analog</p>	<p>Standard M12 mating cable color code:</p> <p>BROWN WHITE BLUE BLACK *GRAY (GREEN/YELLOW)</p>
* 5 pin Standard M12 mating cable must be used: +VDC must be connected to pin 5 if Analog 0-10 VDC is not used.	

## S30 – XXX – RMH —» Part Number Key

<p><b>Product Family:</b> Spot Light 30mm Barrel</p>	<p><b>Color:</b> 625 – Red            IR 850nm White – WHI        IR 940nm 470 – Blue            UV 395nm 505 – Cyan            UV 365nm 530 – Green 590 - Yellow</p>
--	---